

FLEET SERIES

EVERY DAY RELIABILITY. BUILT FOR THE FLEET.

Built with the fleet in mind, Fleet Series work lights deliver dependable output and practical versatility for everyday fleet, utility, and vocational applications. Compact, efficient, and built for daily use, they provide the reliable lighting you need at a value that makes sense.

FULL SERIES LINEUP 8 Models · Round & Square · 1600 - 1800 Effective Lumen



HD36009-3F | HD36009-3S

3.54" x 3.54" x 1.91"

1600

EF LM

9 LEDs • 27W



HD38009-3F | HD38009-3S

3.54" x 1.97"

1600

EF LM

9 LEDs • 27W



HD43009-3F | HD43009-3S

4.31" x 4.31" x 2.32"

1800

EF LM

9 LEDs • 27W



HD44009-3F | HD44009-3S

4.31" x 2.32"

1800

EF LM

9 LEDs • 27W

STANDARD FEATURES

BUILT TO LAST. DESIGNED TO PERFORM.

Fleet Series work lights combine durable construction, efficient output, and practical features in a compact, dependable platform designed for everyday work.

☀️ 3W SMD LEDs Super-bright 3W SMD LEDs deliver compact, high-output illumination.	🏠 DIECAST ALUM. HOUSING Powder-coated diecast aluminum body provides durable construction for everyday fleet use.	⊕ POLYCARBONATE LENS Impact-resistant polycarbonate lens protects the light in demanding work applications.	🔗 S/S MOUNTING HARDWARE Stainless steel mounting hardware provides secure, dependable installation.
🛡️ SEALED ELECTRONICS Sealed, coated electronics help protect internal components from exposure.	⚡ 9-32V / 10-32V Wide-voltage compatibility supports common 12V and 24V vehicle electrical systems.	Ⓢ ECE R10 / CE / RoHS Compliance includes ECE R10, CE and RoHS as specified across the Fleet Series lineup.	🔦 FLOOD & SPOT BEAMS Available in flood and spot patterns for wide-area or focused illumination.

PRODUCT SPECIFICATIONS

FLEET SERIES – PRODUCT SPECIFICATIONS							
PART NO.	SIZE	LEDS	EFF LM	RAW LM	VOLTAGE	WATTS	AMP DRAW
HD36009-3F	3.6" Sq Flood	9	1600	1910	9-32V	27W	1.89A @ 12V, 0.99A @ 24V
HD36009-3S	3.6" Sq Spot	9	1600	1910	9-32V	27W	1.89A @ 12V, 0.99A @ 24V
HD38009-3F	3.6" Rnd Flood	9	1600	1910	9-32V	27W	1.89A @ 12V, 0.99A @ 24V
HD38009-3S	3.6" Rnd Spot	9	1600	1910	9-32V	27W	1.89A @ 12V, 0.99A @ 24V
HD43009-3F	4.3" Sq Flood	9	1800	2250	10-32V	27W	1.7A @ 12V, 0.85A @ 24V
HD43009-3S	4.3" Sq Spot	9	1800	2250	10-32V	27W	1.7A @ 12V, 0.85A @ 24V
HD44009-3F	4.3" Rnd Flood	9	1800	2250	10-32V	27W	1.7A @ 12V, 0.85A @ 24V
HD44009-3S	4.3" Rnd Spot	9	1800	2250	10-32V	27W	1.7A @ 12V, 0.85A @ 24V

AT A GLANCE

8 models

Round & square - one platform

1600–1800 lm

Effective lumen range

3W smd

Light Emmitting Diodes | LEDs

6000K color temp

Clean, bright white output

ECE R10

Electromagnetic compatibility

CERTIFICATIONS & FEATURES

- Super Bright High Power LEDs
- Powder Coated Diecast Alum. Housing
- Stainless Steel Bracket & Mounting Hardware
- 12" Shielded Cable
- Sealed Coated Electronics
- Working Temp: -40° to +50°C
- Color Temp: 6000K
- ECE R10 | CE | RoHs